



# CAMERA CABLE T30

## HD CAMERA CABLE

The T30 camera cable is a robust triple-coax camera cable designed for HD cameras. It is a strong and flexible cable specially designed with Kevlar braid for handling the camera hanging from the cable only.

### APPLICATIONS

- Cable for underwater use or in air together with Ahlberg HD cameras

### BENEFITS

- Equipped with a reterminable connector for use in air and a moulded connector for underwater use
- Specially designed with Kevlar braid for handling the camera hanging from the cable only.

### SPECIFICATIONS


Number of conductors	27 + 3 coaxial
Diameter	10 mm (0,39")
Outer sheath	PUR, frosted
Color	Black
Minimum bend radius, fixed installation	70 mm (2,76")
Minimum bend radius, flexible installation	200 mm (7,87")
Temperature rating	-40°C to +80°C (-40°F to +176°F)
Weight	0,17 kg/m
Water tightness	3,5 bar (35 m )
Ingress protection	IP68 (underwater part)
Tensile strength	1 900 N
Radiation tolerance (total dose)	2 000 000 Gy (200 000 000 rad)

*We reserve the right to alter specifications without prior notice*

## CAMERA CABLE T30 IMAGES



### LINKS

 English

[ahlbergcameras.staging.westart.se/products/cables/camera-cable-t30](https://ahlbergcameras.staging.westart.se/products/cables/camera-cable-t30)

*We reserve the right to alter specifications without prior notice*