



CAMERA CABLE T32

SD CAMERA CABLE

The T32 camera cable is used together with Ahlberg SD and monochrome cameras. It is a flexible and strong cable specially designed with Kevlar braid for handling the camera hanging from the cable only.

APPLICATIONS

- Cable for underwater use or in air together with Ahlberg SD cameras

BENEFITS

- A flexible and strong cable
- Can be equipped with a reterminable connector for use in air and a moulded connector for underwater use
- Specially designed with Kevlar braid for handling the camera hanging from the cable only

SPECIFICATIONS


| | |
|--|----------------------------------|
| Number of conductors | 30 + 2 coaxial |
| Diameter | 12 mm (0,47") |
| Outer sheath | PUR, frosted |
| Color | Black |
| Minimum bend radius, flexible installation | 80 mm (3,15") |
| Temperature rating | -40°C to +80°C (-40°F to +176°F) |
| Weight | 0,26 kg/m |
| Ingress protection | IP68 (underwater part) |
| Water tightness | 3,5 bar (35 m) |
| Tensile strength | 5 000 N |
| Radiation tolerance (total dose) | 2 000 000 Gy (200 000 000 rad) |

We reserve the right to alter specifications without prior notice

CAMERA CABLE T32 IMAGES



LINKS

 English

ahlbergcameras.staging.westart.se/products/cables/camera-cable-t32

We reserve the right to alter specifications without prior notice