



# CCTV CABLE T24

## FIRE RESISTANT CCTV CABLE

T24 is a shielded twisted pair cable used in CCTV installations. It is halogen free and flame resistant. T24 connects the camera/light/microphone/pan&tilt unit with the control unit. The control unit/protocol inverter is usually placed in an adjacent room with a lower degree of radiation.

## APPLICATIONS

- Cable for CCTV use

## BENEFITS

- Fire resistant, Category A according to IEC 60332-3-22:2000

## SPECIFICATIONS


Number of conductors	24 (23+1 coax)
Diameter	13 mm (0,51")
Outer sheath	PUR, frosted
Color	Black
Minimum bend radius, fixed installation	97,5 mm (3,84")
Minimum bend radius, flexible installation	195 mm (7,68")
Temperature rating	-40°C to +80°C (-40°F to +176°F)
Weight	0,26 kg/m
Tensile strength	5 000 N
Radiation tolerance (total dose)	2 000 000 Gy (200 000 000 rad)

*We reserve the right to alter specifications without prior notice*

## CCTV CABLE T24 IMAGES



### LINKS

 English

[ahlbergcameras.staging.westart.se/products/cables/cctv-cable-t24](https://ahlbergcameras.staging.westart.se/products/cables/cctv-cable-t24)

*We reserve the right to alter specifications without prior notice*